



J Series	Ports		std Power	Performance			Execution			Wear Plate	Construction Materials			Single Seal type				Elastomers			
Pump Type	BSP	DN	Kw-50hz	RPM	max m ³ /h	max H m	Bare Shaft	Closed Coupled	ATEX**	No.	Cast Iron	S.Steel Fitted	Full S.Steel	Silicium/Nitri	Silicium/Viton	Silicium/PTFE	Graphite/Viton	Flushing	Nitri	Viton	PTFE
J 1-110	1 1/2"	40	1.1	2900	22	16.5	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 1-160	1 1/2"	40	2.2	2900	20	30	Yes	Yes	-	0	Yes	-	-	Yes	Yes	-	Yes	Yes	Yes	Yes	-
J 1-180	1 1/2"	40	4	2900	25	35	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 2-100	2"	50	1.1	2900	30	14	Yes	Yes	-	0	Yes	-	-	Yes	Yes	-	Yes	-	Yes	Yes	-
J 2-120	2"	50	2.2	2900	40	20	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 2-170	2"	50	4	2900	44	36	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 2-180	2"	50	5.5	2900	50	38	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 2-215	2"	50	11	2900	46	60	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 3-100	3"	80	2.2	2900	60	14	Yes	Yes	-	0	Yes	-	-	Yes	Yes	-	Yes	-	Yes	Yes	-
J 3-140	3"	80	4	2900	80	21	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 3-180	3"	80	7.5	2900	84	35	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 3-210	3"	80	4	1450	95	16	Yes	Yes	Yes	2	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 3-225	3"	80	15	2900	95	55	Yes	-	Yes	2	Yes	Yes	-	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 3-240	3"	80	18.5	2900	80	70	Yes	Yes	Yes	1	Yes	Yes	Yes	Yes	Yes	-	Yes	Yes	Yes	Yes	-
J 3-252	3"	80	22	2900	95	80	Yes	-	Yes	1	Yes	-	-	Yes	Yes	Yes	Yes	Yes	Yes	Yes	-
J 3-305	3"	80	75	2900	105	110	Yes	-	Yes	1	Yes	-	-	Yes	Yes	-	Yes	Yes	Yes	Yes	-
J 4-100	4"	100	4	2900	100	15	Yes	Yes	-	0	Yes	-	-	Yes	Yes	-	Yes	-	Yes	Yes	-
J 4-160	4"	100	11	2900	150	24	Yes	Yes	Yes	1	Yes	Yes	-	Yes	Yes	-	Yes	Yes	Yes	Yes	-
J 4-220	4"	100	5.5	1450	130	15	Yes	Yes	Yes	2	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 4-225	4"	100	22	2900	150	46	Yes	-	Yes	2	Yes	Yes	Yes	Yes	Yes	-	Yes	Yes	Yes	Yes	Yes
J 4-250	4"	100	7.5	1450	160	20	Yes	Yes	Yes	2	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 4-316	4"	100	18.5	1450	170	30	Yes	-	Yes	1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
J 6-250	/	150	11	1450	320	18	Yes	Yes	Yes	2	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	-
J 6-350	/	150	30	1450	310	35	Yes	-	Yes	1	Yes	-	-	-	Yes	-	-	Yes	Yes	Yes	-
J 6-400	/	150	45	1450	380	37	Yes	-	Yes	1	Yes	Yes	Yes	-	Yes	Yes	Yes	Yes	Yes	Yes	-
J 8-300	/	200	22	1450	480	22	Yes	-	Yes	1	Yes	-	-	Yes	Yes	-	-	-	Yes	-	-
J 8-305	/	200	18.5	1450	380	20	Yes	-	Yes	1	Yes	-	-	Yes	Yes	-	-	-	Yes	-	-
J 10-305	/	250	30	1450	600	21	Yes	-	Yes	1	Yes	-	-	-	Yes	-	-	-	Yes	-	-
J 12-385	/	300	55	1450	1000	30	Yes	-	-	2	Yes	-	-	-	Yes	-	-	-	Yes	-	-
J 12-400	/	300	55	975	1200	17	Yes	-	-	2	Yes	-	-	-	Yes	-	-	-	Yes	-	-

ATEX**
= not available in every materials combination