



ST-R - NAMING BARE SHAFT PUMP (SUPPORT - S)

ST-R	2	S	G	1	0	E	+F	EX	-AM10	ACY	VSN	
												<p>PUMP VARIANTS: VISION.. or VSN...: Special executions with dedicated variant/s compared to standard construction. Depending on the following numbering - please contact our office for detailed descriptions. It defines all the construction characteristics of the bare shaft pump not described in the standard codes.</p>
												<p>PAINTING: ACY / BLU / RAL / series of numbers indicating the RAL: different color from standard RAL 5010.</p>
												<p>Standardized special versions: Please contact our office for specific descriptions (AM10, NV,... etc)</p>
												<p>EX: Preparation for ATEX II 2/2G version</p>
												<p>F / FA: ports kit (F: DIN; FA: ANSI)</p>
												<p>E: Shaft extension in millimeters – ISO 228 (BSP) threaded ports for ST-R2, ST-R3, and ST-R4, and ANSI B16.5 Class 150 RF flanged ports (for ST-R6) and DN200 PN16 EN 1092-2 TYPE B (for ST-R8) A: Shaft extension in inches – NPT 228 (BSP) threaded ports for ST-R2, ST-R3, and ST-R4, and ANSI B16.5 Class 150 RF flanged ports (for ST-R6 and ST-R8)</p>
												<p>HEAD FLUSHING FOR SEALING MOTOR 0: version without head flushing for sealing motor</p>
												<p>MECHANICAL SEAL TYPE: 1: carbide mechanical seal, FKM (Viton®) gaskets in oil bath with visual indicator in a dedicated chamber.</p>
												<p>CONSTRUCTION MATERIALS OF THE PUMP: G: cast iron F: cast iron - stainless steel D: cast iron - deep hardening with heat treatment (380 - 420 HB)</p>
												<p>S: Unit with bearing support - free shaft execution</p>
												<p>PUMP MODEL: ports diameter in inches</p>
												<p>ST-R: self-priming centrifugal pump ST-R series</p>

Key:
Highlighted backgrounds: always present in the pump naming
Unhighlighted backgrounds: construction variants and pump accessories