



J Series	Ports		std Power	Performance			Execution			Wear Plate	Construction Materials			Single Seal type		Elastomers	
Pump Type	BSP	DN	Kw-50hz	RPM	max Mc/h	max H m	Bare Shaft	Closed Coupled	ATEX	No.	Cast Iron	S.Steel Fitted	Hard Cast Iron	Silicium/Nitril	Silicium/Viton	Nitril	Viton
ST-R 2	2"	50	7.5	2900	50	36	Yes	-	-	2	Yes	Yes	Yes	-	Yes	Yes	Yes
ST-R 2	2"	50	1.5	1450	34	14	Yes	-	-	2	Yes	Yes	Yes	-	Yes	Yes	Yes
ST-R 3	3"	80	5.5	1450	100	17	Yes	-	-	2	Yes	Yes	Yes	-	Yes	Yes	Yes
ST-R 4	4"	100	11	1450	170	20	Yes	-	-	2	Yes	Yes	Yes	-	Yes	Yes	Yes
ST-R 6	-	150	30	1450	340	30	Yes	-	-	2	Yes	Yes	Yes	-	Yes	Yes	Yes
ST-R 8	-	200	18.5	960	420	19	Yes	-	-	2	Yes	Yes	Yes	-	Yes	Yes	-

Varisco S.r.l.
+39 0498294111
www.varisco.it